

## Datasheet

## 2x2Pt100A-G

112024

### Summary

This platinum temperature sensor element is characterized by its long-term stability over a wide temperature range. They are used particularly in the automotive, air conditioning and heating technology branch and in devices for medicine and industry.

### Dimensions in mm

	<b>L</b>	<b>B</b>	<b>L<sub>1</sub></b>	<b>H</b>	<b>Ø</b>
	2,3 ± 0,15	1,9 ± 0,2	10 ± 1	0,9 +0,3 -0,2	0,2 ± 0,02

### Technical specifications

Nominal resistance R <sub>0</sub> at 0°C	Specification	Tolerance	Order Number	Item Number
100 Ω	DIN EN 60751	F 0,15 (DIN A)	2x2Pt100A-G	112024

Temperature range:	-70 ° C to +500 ° C in continuous operation (briefly up to 550 ° C possible)		
	Validity of tolerance F 0.15: -50 ° C to +300 ° C		
Temperature coefficient:	TK = 3850 ppm / K		
Connecting wires:	PtNi coated wire, suitable for crimping, welding and brazing		
Long-term stability:	Max. R <sub>0</sub> -drift 0.04% after 1000 h at 500 ° C		
Vibration resistance:	At least 40 g acceleration at 10 to 2000 Hz, depends on installation		
Shock resistance:	At least 100 g acceleration with 8ms half sine wave, depends on installation		
Environmental conditions:	unprotected only in dry environments		
Insulation resistance:	> 100 MΩ at 20 ° C; > 2 MΩ at 500 ° C		
Self-heating:	0.4 K / mW at 0 ° C		
Response:	water current (v = 0.4 m / s):	τ <sub>0,5</sub> = 0.05 s	τ <sub>0,9</sub> = 0.15 s
	Air flow (v = 2 m / s):	τ <sub>0,5</sub> = 3.0 s	τ <sub>0,9</sub> = 10.0 s
Measuring current:	0.3 to 1 mA (consider self-heating)		
Measuring point:	8 mm from the end of the sensor element body		
Packaging:	loose packed in bag / vacuum.		
<b>Note:</b>	<b>Please refer to our application and installation instructions.</b>		
RoHS compliant			

Technische Änderungen behalten wir uns vor. Alle technischen Angaben sind Beschaffenheitsangaben und sichern keine Eigenschaften zu.

Version 1.0 vom 06/2012

